

Deck Mounted Bath Shower Mixer





Product features:


- Metal & ABS construction
- Custom designed for lower range pressures
- · Double linked shower hose for ultimate durability
- · Single spray pattern showerhead
- · Rub clean anti limescale spray nozzles

Packaged properties:

Box length: 250 mm **Box depth:** 155 mm **Box width:** 155 mm **Boxed weight:** 3.19 kg

Includes pop up waste?: No Additional comments:
Rounded fixed shower bracket

Product dimensions:



• Overall Height / projection: 92 mm

Exit reach: 100 mmExit height: 27 mm


• Centre distance(s): 180 mm

• Base diameter(s): 50 mm

Product mounted where: Surface
Recommended hole diameter:
Min. fitting depth required:

• Max. surface depth: 30 mm

Product flow characteristics:



• Min / Max water pressure: 0.2 bath & 0.4 shower / 5 bar • Part G mixed flow rate at 3 bar (I/m): bath>44, shower>16.1

• Max water temperature: 70° C

Product flow characteristics: Single flow
 Aerator type: Chromed flow straightener

• Includes output diverter?: Yes

• Control valve type: 3/4" QT CD (8-20)

• Non return valve position: no nrv supplied

Mesh particle filter size:
Inlet / outlet size: 3/4" M /

• Inlet type / length: Fixed / 50 mm

• Shower hose type / length: Steel linked / 1.50 m

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 2 years
- Surface warranty defects warranted for 1 year
 O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives