

# **Fervour**

# Tall Basin Single Lever c/w PUW Short Reach



## Product features:


- · Metal construction throughout
- Leading design features requiring high pressure
- Single lever control for effortless single handed control
- · Fixed spout to prevent accidental water damage
- · Elegant minimalist design styling with a softened edge

Packaged properties:

Box length: 360 mm Box depth: 100 mm Box width: 195 mm Boxed weight: 3.29 kg Includes pop up waste?: Yes

**Additional comments:** 

#### **Product dimensions:**



• Overall Height / projection: 296 mm


• Exit reach: 129 mm • Exit height: 244 mm Centre distance(s):

• Base diameter(s): [] 50 mm • Product mounted where: Surface

• Recommended hole diameter: Ø 33.5 mm

• Min. fitting depth required: • Max. surface depth: 70 mm

### Product flow characteristics:



- Min / Max water pressure: 1.50 / 5 bar • Part G mixed flow rate at 3 bar (I/m): 9.3
- Max water temperature: 70° C
- Product flow characteristics: Single flow
- Aerator type: Plastic honeycomb • Includes output diverter?: No
- Control valve type: Single lever (30mm)
- Non return valve position:
- Mesh particle filter size: Inlet / outlet size: 1/2" F / M8 • Inlet type / length: Flexi / 620 mm
- Shower hose type / length:

#### Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 2 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

#### Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- $Residues \ of \ liquid \ soaps, \ shampoos \ and \ shower \ foams \ can \ also \ cause \ damage, \ so \ rinse \ with \ clean$ water after using, avoid contact with any abrasives