





Product features:

- Metal & ABS construction
- Single lever control for effortless single handed control
- · Leading design features requiring high pressure
- · Fixed spout to prevent accidental water damage
- · Non-adjustable exit height


Packaged properties:

Box length: 1280 mm **Box depth:** 235 mm **Box width:** 570 mm **Boxed weight:** 14.06 kg

Includes pop up waste?: No Additional comments:

Includes mesh filter, 2.5mm allen key. ABS showerhead

Product dimensions:




• Overall Height / projection: 1076 mm

Exit reach: 245 mm
Exit height: 810 mm
Centre distance(s):

Base diameter(s): [] 110 mm
Product mounted where: Floor
Recommended hole diameter:
Min. fitting depth required: 60 mm

• Max. surface depth:

Product flow characteristics:



- Min / Max water pressure: 1 bath & 0.75 shower / 5 bar
- Part G mixed flow rate at 3 bar (I/m): bath=16.25, shower=14.2

• Max water temperature: 70° C

• Product flow characteristics: Single flow

Aerator type: Plastic honeycomb
Includes output diverter?: Yes
Control valve type: Single lever ()

• Non return valve position: sprayhead exit

• Mesh particle filter size: 0.60 mm

Inlet / outlet size: 1/2" F /Inlet type / length: / mm

• Shower hose type / length: Smoothflex / 1.50 m

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 2 years
- Surface warranty defects warranted for 1 year
 O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- Regular cleaning will prevent the build up of lime scale and diff
 After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives