

Euphoria

Square Low Pressure Thermostatic Bar Shower



Product features:


- Metal & ABS construction
- · Thermostatic valve for safety & comfort
- · Minimalist planate design form
- · Supplied with adjustable centre inlets
- · Luscious European quality chromium plate finish

Packaged properties:

Box length: 380 mm **Box depth:** 75 mm **Box width:** 175 mm **Boxed weight:** 3.02 kg

Includes pop up waste?: No Additional comments:

Product dimensions:



• Overall Height / projection: 105 mm


Exit reach:Exit height:

• Centre distance(s): 150 ± 20 mm

Base diameter(s): [] 60 mm
Product mounted where: Wall
Recommended hole diameter:
Min. fitting depth required: 60 mm

· Max. surface depth:

Product flow characteristics:



- Min / Max water pressure: 0.20 / 5 bar
 Part G mixed flow rate at 3 bar (I/m): 34
- Max water temperature: 70° C • Product flow characteristics:
- Aerator type:
- Includes output diverter?: No
 Control valve type: Thermostatic ()
 Non return valve position: h&c inlet
 Mesh particle filter size: 0.60 mm
- Inlet / outlet size: 1/2" M /
- Inlet type / length: Eccentric / 50 mm
- Shower hose type / length:

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 2 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives