

# Euphoria

## Thermostatic 1 Exit Concealed Shower (Serenitie)



### Product features:


- Metal & ABS construction
- Custom designed for lower range pressures
- Thermostatic valve for safety & comfort
- 5 year limited warranty
- · Modern minimalism with flair

Packaged properties:

**Box length:** 270 mm **Box depth:** 155 mm **Box width:** 235 mm **Boxed weight:** 2.85 kg


Includes pop up waste?: No Additional comments:

#### **Product dimensions:**



- Overall Height / projection: 70 mm
- Exit reach:
- Exit height:
- Centre distance(s):
- Base diameter(s): 155 x 234 mm
  Product mounted where: Wall
  Recommended hole diameter:
  Min. fitting depth required: 53-65 mm
- Max. surface depth:

## **Product flow characteristics:**



- Min / Max water pressure: 0.20 / 5 bar
   Part G mixed flow rate at 3 bar (I/m): 35
- Max water temperature: 70° C
  Product flow characteristics:
- Aerator type:
- Includes output diverter?: No
  Control valve type: Thermostatic ()
  Non return valve position: h&c inlet
  Mesh particle filter size: 0.60 mm
  Inlet / outlet size: 1/2" M / 1/2" M
  Inlet type / length: Fixed / mm
- Shower hose type / length:

#### Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 2 years
- Surface warranty defects warranted for 1 year
   O-rings, hoses & gaskets warranted for 1 year

#### Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives