

Euphoria

Thermostatic 2 Exit Concealed Shower (Harmonie)




Product features:

- Metal & ABS construction
- · Thermostatic valve for safety & comfort
- 2 exit alternate control for output to 2 x shower or 1 x shower & 1 x bath
- · A modern design classic style
- 5 year limited warranty

Packaged properties:

Box length: 270 mm Box depth: 155 mm Box width: 235 mm Boxed weight: 2.72 kg Includes pop up waste?: No **Additional comments:**

Product dimensions:




- Overall Height / projection: 52 mm
- Exit reach:
- Exit height:
- Centre distance(s):

• Base diameter(s): 155 x 234 mm • Product mounted where: Wall • Recommended hole diameter:

• Min. fitting depth required: 58-68 mm

• Max. surface depth:

Product flow characteristics:



• Min / Max water pressure: 0.50 / 5 bar • Part G mixed flow rate at 3 bar (I/m): 16.7

• Max water temperature: 70° C Product flow characteristics:

Aerator type: • Includes output diverter?: Yes • Control valve type: Thermostatic () • Non return valve position: h&c inlet • Mesh particle filter size: 0.60 mm Inlet / outlet size: 1/2" M / 1/2" M • Inlet type / length: Fixed / mm

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 2 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt

· Shower hose type / length:

- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- $Residues \ of \ liquid \ soaps, \ shampoos \ and \ shower \ foams \ can \ also \ cause \ damage, \ so \ rinse \ with \ clean$ water after using, avoid contact with any abrasives