abode



0000e	Thermostatic 2 Exit Concealed Shower (Serenitie)
OFF ON	 Product features: Metal & ABS construction Thermostatic valve for safety & comfort 2 exit alternate control for output to 2 x shower or 1 x shower & 1 x bath Freshly designed contemporary blend 5 year limited warranty
Packaged properties:Box length: 270 mmBox depth: 155 mmBox width: 235 mmBoxed weight: 2.56 k	Includes pop up waste?: No Additional comments:
Product dimensions:	 Overall Height / projection: 59 mm Exit reach: Exit height: Centre distance(s): Base diameter(s): 155 x 234 mm Product mounted where: Wall Recommended hole diameter: Min. fitting depth required: 58-68 mm Max. surface depth:
<figure></figure>	 Min / Max water pressure: 0.50 / 5 bar Part G mixed flow rate at 3 bar (l/m): 16.7 Max water temperature: 70° C Product flow characteristics: Aerator type: Includes output diverter?: Yes Control valve type: Thermostatic () Non return valve position: h&c inlet Mesh particle filter size: 0.60 mm Inlet / outlet size: 1/2" M / 1/2" M Inlet type / length: Fixed / mm Shower hose type / length:
Warranty Summary (Full details available on request): C • Materials and workmanship defects warranted for 5 years • • Valves and working parts warranted for 2 years • • Surface warranty defects warranted for 1 year • • O-rings, hoses & gaskets warranted for 1 year •	are instructions: Clean the mixers and showers regularly as required, using soap, do not use any other cleaners. Regular cleaning will prevent the build up of lime scale and dirt After cleaning rinse thoroughly with clean water to remove any cleaner residue Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives