

# Tubular shower head Kit (Roof)





#### Product features:

- · Metal construction throughout
- · Single spray pattern showerhead
- Swivel showerhead connector for maximum flexibility
- The perfect combination of European design styles


Packaged properties:

Box length: mm Box depth: mm

Box width: mm Boxed weight: 0.97 kg

Includes pop up waste?: No Additional comments: See AB2415 & AB2409

### **Product dimensions:**



• Overall Height / projection: 370 mm

• Exit reach: 370 mm

Exit height:


• Centre distance(s):

Base diameter(s): 65 mm
Product mounted where: Roof
Recommended hole diameter:

• Min. fitting depth required:

• Max. surface depth:

## **Product flow characteristics:**



• Min / Max water pressure: 0.30 / 5 bar • Part G mixed flow rate at 3 bar (I/m): 14.64

Max water temperature: 70° C
Product flow characteristics:

Aerator type:

• Includes output diverter?: No

• Control valve type: ()

Non return valve position:

Mesh particle filter size:

Inlet / outlet size: 1/2" F / 1/2" M
Inlet type / length: Fixed / mm
Shower hose type / length:

#### Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 2 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year

## Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives