





## Product features:

- Metal & ABS construction
- Rub clean anti limescale spray nozzles
- · Multi spray pattern showerhead
- Swivel showerhead connector for maximum flexibility
- The perfect combination of European design styles


Packaged properties:

Box length: mm Box depth: mm

Box width: mm Boxed weight: 0.59 kg

Includes pop up waste?: No Additional comments: See AB2418 & AB2412

### **Product dimensions:**




• Overall Height / projection: 230 mm

Exit reach: 165 mm
Exit height: 110 mm
Centre distance(s):

Base diameter(s): 60 mm
Product mounted where: Wall
Recommended hole diameter:
Min. fitting depth required:

• Max. surface depth:

## Product flow characteristics:



- Min / Max water pressure: 0.00 / 5 bar
   Part G mixed flow rate at 3 bar (I/m): 13.36
- Part G mixed flow rate at 3 par (I/m): 13.36

Max water temperature: 70° C
 Product flow characteristics:

Aerator type:

• Includes output diverter?: No

• Control valve type: ()

Non return valve position:

Mesh particle filter size:

• Inlet / outlet size: 1/2" M / 1/2" M • Inlet type / length: Fixed / mm

· Shower hose type / length:

# Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 2 years
- Surface warranty defects warranted for 1 year
   O-rings, hoses & gaskets warranted for 1 year

### Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- Regular cleaning will prevent the build up of lime scale and diff
   After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives