

# Euphoria

## Fervour / Zeal Square Wall Mounted Thermostatic Shower



#### Product features:

- Metal & ABS construction
- · Leading design features requiring high pressure
- Thermostatic valve for safety & comfort
- · Single spray pattern showerhead
- · Swivel showerhead connector for maximum flexibility


Packaged properties:

**Box length:** 1260 mm **Box width:** 550 mm **Box depth:** 200 mm **Boxed weight:** 16.58 kg

Includes pop up waste?: No Additional comments:

Includes 3mm allen key, ABS handshower

#### **Product dimensions:**



• Overall Height / projection: 1774 mm


• Exit reach: 390 mm • Exit height: 1702 mm

• Centre distance(s): 150 ± 20 mm

Base diameter(s): 63 mm
Product mounted where: Wall
Recommended hole diameter:
Min. fitting depth required:

• Max. surface depth:

### **Product flow characteristics:**



- Min / Max water pressure: 1.5 min. & 3 pref. / 5 bar
   Part G mixed flow rate at 3 bar (I/m): 13.9
- Max water temperature: 70° C
  Product flow characteristics:
- Aerator type:
- Includes output diverter?: YesControl valve type: Thermostatic ()
- Non return valve position: h&c inlet & shower snodo
- Mesh particle filter size: 0.60 mm
  Inlet / outlet size: 1/2" M / 3/4" M
  Inlet type / length: Eccentric / mm
- Shower hose type / length: Smoothflex / 1.50 m

#### Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 2 years
- Surface warranty defects warranted for 1 year
   O-rings, hoses & gaskets warranted for 1 year

#### Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives