

Monument Tools Ltd.  
Restmor Way • off Hackbridge Road  
Hackbridge • Wallington • Surrey  
SM6 7AH • United Kingdom

Tel : +44 (0)20 8288 1100  
Fax : +44 (0)20 8288 1108  
Email : info@monument-tools.com

**MONUMENT** © 2002  
[www.monument-tools.com](http://www.monument-tools.com)

*Over 70 years of excellence as hand tool manufacturers and distributors of equipment for the plumbing and drainage industry  
Registered in England at the above address, certificate no. 281817. VAT Registered No. GB 217 8102 81*

## PRODUCT INSTRUCTIONS

Product Code	<b>450P</b>	Product Description	<b>Four bushes included to fit most ½" and ¾" taps. Three hardened cutters for ½" and ¾" taps.</b>
Product Code	<b>451S</b>	Product Description	<b>DIY Tap Reseater † with 19 &amp; 22mm (¾", 7/8") flat cutters and two double ended plastic bushes</b>

## SHUT OFF WATER BEFORE STARTING THE JOB

### TOOLS REQUIRED

A screwdriver, a spanner and (if shields are fitted) water pump pliers or similar tool and a torch.

- If the tap is shielded and is loose enough, unscrew it by hand. If not, use the water pump pliers, but on plated taps these should be padded to avoid damage. (On some taps the handle may have to be removed before the shield can be unscrewed, on others the handle acts as a shield, so only the handle need be removed).
- Select the bush which will screw directly into the female threaded tap body.
- Put this bush on the center spindle of the tool, so that the threaded portion to be used is downwards at the cutter end of the tool.
- Attach the cutter to be used, ensuring that it is screwed completely on to the threaded end of the centre spindle.
- Insert the cutter and the bush into the tap body, screwing the bush home into the body thread.
- Holding the plastic knob at the top of the tool, and with light downward pressure, turn the knob clockwise so that the cutter removes a small amount of seat. Make sure the cutter does this without vibration. Five or six complete turns is normally adequate. Examine the seat to make sure that it is re-cut smoothly. The torch may be useful to examine the seat.
- If necessary fit a new washer.
- Replace tap assembly.

† 451S DIY Tap Reseater is not for use in the UK



Member  
**COMITÉ EUROPÉEN DE L'OUTILLAGE**  
EUROPEAN TOOL COMMITTEE • EUROPÄISCHES WERKZEUGKOMITEE

