

## FLEXIBLE PLUG & CANVAS AIR BAG SPECIFICATIONS

### FLEXIBLE PLUGS

Durable quality with peripheral ribs, fitted with Schrader valve.

Product Code	Diameter		Maximum allowable back pressure	
	inch	range mm	psi	Bar
1287X	1"		45	3
1288A	2"	50-71	14.0	0.97
1289D	3"	71-91	10.0	0.69
1290H	4"	91-142	8.5	0.59
1291K	6"	142-200	7.5	0.52
1297C	8-12"	200-320	6.0	0.41

NOTE:

- Inflate slowly.

### AIR BAG STOPPERS

Canvas outer casing with rubber bladder inside.

Product Code	Diameter		Maximum allowable back pressure	
	inch	range mm	psi	Bar
1477A <sup>2</sup>	2"	51-54	10.0	0.69
1478D <sup>2</sup>	3"	76-81	10.0	0.69
1472L <sup>2</sup>	4"	101-107	10.0	0.69
1479G <sup>1</sup>	4"	101-107	10.0	0.69
1481N <sup>2</sup>	6"	152-161	7.5	0.52
1482Q <sup>2</sup>	9"	229-242	5.0	0.35
1483T <sup>2</sup>	12"	305-323	5.0	0.35

<sup>1</sup> Fitted with Schrader valve

<sup>2</sup> Fitted with Brass valve

NOTE:

- Inflate slowly
- At maximum inflation. the sealing area is restricted and reduces the maximum allowable back pressure

